MERCEDES-BENZ (EU) SL-CLASS R230 SL 280 230.454 (2008-2009)



| 01 (50001 (10 11 | | |
|--------------------------------------|--------------------------|--------------------------|
| Helar 0W-40 | Emperol 5W-40 | Emperol 5W-50 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Normal | | Moderate |
| USE | | CLIMATE |
| Change every 25000 km/ 12 months | | |
| Helar 0W-40 | | |
| PRODUCT RECOMMENDATION 1 | | |
| Extended | | Moderate |
| USE | | CLIMATE |
| ENGINE M272.949 Capacity: 8 liter | | |

Change every 15000 km/ 12 months

| DIFFERENTIAL REAR Capacity: 1,1-1,9 liter | | |
|---|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Gear 1071 | Gearlube LS 80W-90 | |

| TRANSMISSION AUTOMATIC 722.9xx 7. Capacity: 9 liter | /1 | |
|--|----|----------|
| USE | | CLIMATE |
| First change only | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 4026 | | |
| Change aver (COOOO line | | |

Change every 60000 km

| HYDRAULIC SYSTEM CONVERTIBLE R Capacity: 0,13 liter | DOF | |
|--|-----|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Fluid 3023 | | |
| | | |

MERCEDES-BENZ (EU) SL-CLASS R230 SL 280 230.454 (2008-2009)



| HYDRAULIC BRAKE SYSTEM ABS Capacity: 1,4-2,25 liter | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Drauliquid-S DOT 4 | |

Change every 24 months

| POWER STEERING Capacity: 1,25 liter | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| | |

| COOLING SYSTEM Capacity: 7,5 liter | | |
|---------------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 11 | Coolant SP 12 EVO | |
| 01 | с | • |

Change every 250000 km/ 180 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.