

MERCEDES-BENZ (EU) SLK-CLASS R170

SLK 230 KOMPRESSOR (1996-1997)



ENGINE M111
Capacity: 5,5 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >2200 Change every 15000 km/ 12 months

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Emperol 5W-40

PRODUCT RECOMMENDATION 2

Emperol 10W-40

PRODUCT RECOMMENDATION 3

Bi-Turbo 15W-40

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >2200 Change every 15000 km/ 12 months

DIFFERENTIAL REAR
Capacity: 0,7 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071

PRODUCT RECOMMENDATION 2

Gearlube LS 80W-90

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >2200 Check every 30000 km

DIFFERENTIAL REAR LIMITED SLIP
Capacity: 1,1 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071

PRODUCT RECOMMENDATION 2

Gearlube LS 80W-90

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >2200 Check every 30000 km

MERCEDES-BENZ (EU) SLK-CLASS R170

SLK 230 KOMPRESSOR (1996-1997)



TRANSMISSION AUTOMATIC 722.6xx 5/1

Capacity: 8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >22000 km ago: Service B. Check every 30000 km

TRANSMISSION MANUAL 5/1

Capacity: 1,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 4026	SP Matic 2032	ATF-A

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >22000 km ago: Service B. Check every 30000 km

HYDRAULIC LEVELLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3023		

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >22000 km ago: Service B. Check every 30000 km

HYDRAULIC SYSTEM CONVERTIBLE ROOF

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3023		

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >22000 km ago: Service B. Check every 30000 km

MERCEDES-BENZ (EU) SLK-CLASS R170

SLK 230 KOMPRESSOR (1996-1997)



HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >22000 Change every 24 months

POWER STEERING

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4026	SP Matic 2032	

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >22000 Check every 30000 km

COOLING SYSTEM

Capacity: 8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >22000 Change every 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.