MERCEDES-BENZ (EU) SLS AMG C197 SLS AMG 197.377/477 (2010-2012)



ENGINE M159.980 Capacity: 9,5 liter		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar MSP+ 5W-40	Specialsynth MSP 5W-40	Helar 0W-40

Change every 20000 km

DIFFERENTIAL REAR

Capacity: 2,9 liter, Capacity: 3,72 liter (+ heat exchanger)

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSAXLE SEMI-AUTOMATIC 700.400 7/1 Capacity: 7 liter, Capacity: 7,8 liter (+ heat exchanger)				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 2072				
Change every 60000 km/ 48 months				

HYDRAULIC BRAKE SYSTEM Capacity: 0,71-0,83 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-S DOT 4	
Change every 24 months	- -

 POWER STEERING

 Capacity: 1 liter

 use
 CLIMATE

 Normal
 Moderate

 PRODUCT RECOMMENDATION 1

 SP Fluid 3013

MERCEDES-BENZ (EU) SLS AMG C197 SLS AMG 197.377/477 (2010-2012)



COOLING SYSTEM Capacity: 14 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 11	Coolant SP 12 EVO	

Change every 250000 km/ 180 months

AIRCONDITIONING COMPRESSOR Capacity: 120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM Capacity: 780 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.