

MERCURY MOUNTAINEER MOUNTAINEER

4.6 V8 24V AWD (2001-2008)

**ENGINE**

Capacity: 5,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Duranza ECO 5W-20*Check every 1 months, change every 5000 miles/ 6 months*

USE

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Duranza ECO 5W-20*Check every 1 months, change every 3000 miles/ 3 months***DIFFERENTIAL FRONT (4x4)**

Capacity: 1,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Change every 150000 miles***DIFFERENTIAL REAR**

Capacity: 1,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140*Change every 100000 miles*

USE

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140*Change every 50000 miles*

MERCURY MOUNTAINEER MOUNTAINEER

4.6 V8 24V AWD (2001-2008)



TRANSFERBOX (4X4)

Capacity: 1,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Change every 150000 miles

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Change every 60000 miles

TRANSMISSION AUTOMATIC 6R60 5/1

Capacity: 10,6 liter (Dry fill)

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Check every 15000 miles, change every 30000 miles

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 15000 miles, change every 24 months

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Check every 6 months

MERCURY MOUNTAINEER MOUNTAINEER

4.6 V8 24V AWD (2001-2008)

**COOLING SYSTEM**

Capacity: 11,5 liter, Capacity: 13,2 liter (With auxiliary climate control)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant SP 11	

Check every 15000 miles/ 6 months, change every 45000 miles

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.