MG METRO METRO 1300 (1986-1989)



| ENGINE/TRANSAXLE MANUAL Capacity: 4,8 liter, Filter capacity: 0,3 liter | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Bi-Turbo 20W-50 | | |
| Change every 20000 km/ 12 months | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Asyntho 5W-30 | Emperol 10W-40 | Bi-Turbo 15W-40 |
| Change every 20000 km/ 12 months | | |
| USE | | CLIMATE |
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Emperol 5W-40 | | |
| Change every 20000 km/ 12 months | | |
| | | |

| HYDRAULIC BRAKE SYSTEM | |
|----------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Drauliquid DOT 3 | |
| Change every 30000 km/ 18 months | |

| GREASE POINTS/NIPPLES | | |
|------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

MG METRO METRO 1300 (1986-1989)



| COOLING SYSTEM Capacity: 4,8 liter | | |
|--|--|---------------------|
| use Normal | | climate Moderate |
| PRODUCT RECOMMENDATION 1 Coolant -38 Organic NF | | |
| | | |

Change every 40000 km/ 48 months

| CARBURETTOR DAMPER | | |
|--------------------|--|--|
| CLIMATE | | |
| Mediterranean | | |
| | | |
| | | |
| | | |

Check every 20000 km/ 12 months

| USE | | CLIMATE |
|--------------------------|--------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Asyntho 5W-30 | Emperol 10W-40 | Bi-Turbo 15W-40 |

Check every 20000 km/ 12 months

| USE | | CLIMATE |
|---------------------------------|--|---------|
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Emperol 5W-40 | | |
| Check every 20000 km/ 12 months | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.