

**MG MG-F / MG-TF MG-TF 1.6I (2001-2005)****ENGINE K 1.6**

Capacity: 5 liter (Dry fill), Capacity: 4,5 liter (Service fill)

USE	CLIMATE
Normal	Mediterranean

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 15W-40**

## PRODUCT RECOMMENDATION 2

**Bi-Turbo 20W-50***Change every 20000 km/ 12 months*

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

## PRODUCT RECOMMENDATION 2

**Emperol 10W-40***Change every 20000 km/ 12 months*

USE	CLIMATE
Normal	Arctic

## PRODUCT RECOMMENDATION 1

**Emperol 5W-40***Change every 20000 km/ 12 months*

USE	CLIMATE
Severe	Mediterranean

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 15W-40**

## PRODUCT RECOMMENDATION 2

**Bi-Turbo 20W-50***Change every 12500 km/ 6 months*

USE	CLIMATE
Severe	Moderate

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

## PRODUCT RECOMMENDATION 2

**Emperol 10W-40***Change every 12500 km/ 6 months*

USE	CLIMATE
Severe	Arctic

## PRODUCT RECOMMENDATION 1

**Emperol 5W-40***Change every 12500 km/ 6 months*

**MG MG-F / MG-TF MG-TF 1.6l (2001-2005)****TRANSAXLE MANUAL 5/1**

Capacity: 2,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Gear 5015</b>		

Check every 20000 km/ 12 months, change every 160000 km

**HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

Check every 20000 km, change every 24 months

**COOLING SYSTEM**

Capacity: 10,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

Check every 20000 km/ 12 months, change every 48 months

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant -38 Organic NF</b>		

Check every 20000 km/ 12 months, change every 48 months

**AIRCONDITIONING**

We are unable to give a standard recommendation for this component. Please contact our service department.

**AIRCONDITIONING COMPRESSOR**

Capacity: 140 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.