Change every 12500 km/6 months

MG MG-ZT MG-ZT 190 V6-24V (2001-2005)



| ENGINE 2.5 KV6 Capacity: 5,19 liter | | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Emperol 5W-40 Emperol Racing 10W-60 | | Asyntho 5W-30 |
| Change every 25000 km/ 12 months | | |
| USE | | CLIMATE |
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 | | PRODUCT RECOMMENDATION 3 |
| Emperol 5W-40 Emperol Racing 10W-60 | | Asyntho 5W-30 |

| TRANSAXLE AUTOMATIC Jatco 5/1 Capacity: 4 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Matic 2032 | |

Check every 25000 km/ 12 months, change every 100000 km/ 48 months

| TRANSAXLE MANUAL 5/1 Capacity: 1,4 liter | | | |
|---|----|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | | | |
| SP Gear 5015 | | | |
| 01 1 050001 /10 11 | -1 | | |

Check every 25000 km/ 12 months, change every 150000 km/ 72 months

| HYDRAULIC BRAKE/CLUTCH SYST Capacity: 1 liter (Dry fill) | EM | | |
|--|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Drauliquid-LV Super DOT 4 Drauliquid-S DOT 4 | | | |
| Check every 25000 km/ 12 months ch | ange every 24 months | | |

Check every 25000 km/ 12 months, change every 24 months

MG MG-ZT MG-ZT 190 V6-24V (2001-2005)



| POWER STEERING Capacity: 0,35 liter | | |
|-------------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Matic 2032 | ATF Almirol | ATF Dexron II-D |
| Check every 25000 km/ 12 months | | |

| GREASE POINTS/NIPPLES | | |
|---------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 | Multi Purpose Grease 3 |
| Check every 25000 km/ 12 months | | |

| COOLING SYSTEM Capacity: 7,5 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Coolant -38 Organic NF | |
| Check every 25000 km/ 12 months, change every 48 mo | unths |

AIRCONDITIONING

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR Capacity: 140 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.