

MINI (EU) MINI F55/F56 MINI ONE FIRST (55 KW) (2014-2017)

**ENGINE B38A12**

Capacity: 4,25 liter (Service fill), Filter capacity: 0,3 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 0W-20	Presteza MSP 0W-30	Helar SP LL-03 0W-30

*Change every 30000 km/ 24 months***TRANSAXLE AUTOMATIC GA6F21/22FT (Aisin) 6/1**

Capacity: 5,5 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

TRANSAXLE MANUAL GS6-58BG/DG 6/1

Capacity: 1,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		

HYDRAULIC BRAKE/CLUTCH SYSTEM DSC

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Change every 24 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Change every 36 months

MINI (EU) MINI F55/F56 MINI ONE FIRST (55 KW) (2014-2017)



COOLING SYSTEM

Capacity: 4,9-5,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.