

MINI (EU) MINI R50/R53 MINI ONE 1.6 (2004-2006)



ENGINE W10B16
Capacity: 4,5 liter

USE

Flexible (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Helar SP LL-03 5W-30

PRODUCT RECOMMENDATION 2

Presteza MSP 5W-30

PRODUCT RECOMMENDATION 3

Helar MSP+ 5W-40*Change every 24 months*

TRANSAXLE AUTOMATIC GA6F21AW (Aisin) 6/1
Capacity: 6 liter (Dry fill), Capacity: 4,5 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

TRANSAXLE AUTOMATIC GACVT16Z (CVT)
Capacity: 5 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4016*Change every 45000 km*

TRANSAXLE MANUAL GS5-52 BG Getrag 5/1
Capacity: 1,7 liter

USE

07/2004->

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Change every 24 months*

MINI (EU) MINI R50/R53 MINI ONE 1.6 (2004-2006)



HYDRAULIC BRAKE/CLUTCH SYSTEM DSC

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Change every 24 months

ELECTRO-HYDRAULIC POWER STEERING (EHPS)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

POWER STEERING (ATF CAP)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

COOLING SYSTEM

Capacity: 5,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Change every 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.