

MITSUBISHI (EU) ASX / RVR GA0 ASX / RVR 1.6 CLEARTEC (2010-2017)



MOTOR 4A92

Kapacitet: 4,2 liter, Filterkapacitet: 0,2 liter

ANVEND

Foretrukne

KLIMA

Moderat

PRODUKTANBEFALING 1

Presteza MSP 0W-20

Skift alle 20000 km/ 12 måneder

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 20000 km/ 12 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Presteza MSP 0W-30

PRODUKTANBEFALING 2

Avanza MSP 0W-30

PRODUKTANBEFALING 3

Presteza MSP 5W-30

Skift alle 20000 km/ 12 måneder

ANVEND

Krævende

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 10000 km

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

Presteza MSP 0W-30

PRODUKTANBEFALING 2

Avanza MSP 0W-30

PRODUKTANBEFALING 3

Presteza MSP 5W-30

Skift alle 10000 km

MITSUBISHI (EU) ASX / RVR GA0 ASX / RVR 1.6 CLEARTEC (2010-2017)



TRANSAKSEL MANUEL F5M43 5/1

Kapacitet: 2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

Kontroller alle 20000 km/ 12 måneder, skift alle 100000 km

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

Kontroller alle 20000 km/ 12 måneder, skift alle 40000 km

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Kontroller alle 20000 km/ 12 måneder, skift alle 40000 km/ 24 måneder

HYDRAULISK KOBLINGSSYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Kontroller alle 20000 km/ 12 måneder, skift alle 40000 km/ 24 måneder

MITSUBISHI (EU) ASX / RVR GA0 ASX / RVR 1.6 CLEARTEC (2010-2017)



KØLESYSTEM

Kapacitet: 0,65 liter (Reservetank), Kapacitet: 6 liter (Total)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 40000 km/ 24 måneder, skift alle 120000 km/ 72 måneder

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 40000 km/ 24 måneder, skift alle 180000 km/ 108 måneder

KLIMAANLÆGSKOMPRESSOR

Kapacitet: 70-90 cm³

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KLIMAANLÆGSSYSTEM

Kapacitet: 480-520 gram

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.