

MITSUBISHI (EU) COLT CZ3/5 COLT 1.5 DI-D HP (2004-2008)



MOTOR 639939

Kapacitet: 5,5 liter, Filterkapacitet: 0,3 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 20000 km/ 12 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar 0W-40

PRODUKTANBEFALING 2

Emperol 5W-40

PRODUKTANBEFALING 3

Emperol 10W-40

Skift alle 20000 km/ 12 måneder

ANVEND

Krævende

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 10000 km

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar 0W-40

PRODUKTANBEFALING 2

Emperol 5W-40

PRODUKTANBEFALING 3

Emperol 10W-40

Skift alle 10000 km

TRANSAKSEL HALVAUTOMATISK F6SGA 6/1

Kapacitet: 1,75 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Syngear 75W-90

Kontroller alle 20000 km/ 12 måneder, skift alle 200000 km/ 120 måneder

MITSUBISHI (EU) COLT CZ3/5 COLT 1.5 DI-D HP (2004-2008)

**TRANSAKSEL MANUEL F5MGB 5/1**

Kapacitet: 1,75 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90

Kontroller alle 20000 km/ 12 måneder, skift alle 200000 km/ 120 måneder

ANVEND		KLIMA
Krævende		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90

Kontroller alle 20000 km/ 12 måneder, skift alle 100000 km/ 60 måneder

HYDRAULISK BREMSE-/KOPLINGSSYSTEM ABS

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontroller alle 20000 km/ 12 måneder, skift alle 40000 km/ 24 måneder

KØLESYSTEM

Kapacitet: 6,6 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant -38 Organic NF		

Kontroller alle 40000 km/ 24 måneder, skift alle 60000 km/ 48 måneder

KLIMAANLÆGSKOMPRESSORKapacitet: 100 cm³

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.