

MITSUBISHI (EU) GALANT VI GALANT 1.6 (1987-1990)



MOTOR 4G32

Kapacitet: 3,9 liter, Filterkapacitet: 0,4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Emperol 10W-40	Classic Racing Oil 15W-50	Bi-Turbo 15W-40

Skift alle 10000 km/ 6 måneder

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1		
Asyntho 5W-30		

Skift alle 10000 km/ 6 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Emperol 10W-40	Classic Racing Oil 15W-50	Bi-Turbo 15W-40

Skift alle 5000 km

ANVEND	KLIMA
Krævende	Koldt

PRODUKTANBEFALING 1		
Asyntho 5W-30		

Skift alle 5000 km

TRANSAKSEL MANUEL 5/1

Kapacitet: 1,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Syngear 75W-90	

Kontroller alle 20000 km/ 24 måneder, skift alle 80000 km/ 96 måneder

HYDRAULISK BREMSESYSYSTEM

Kapacitet: 0,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Drauliquid DOT 3		

Skift alle 40000 km/ 48 måneder

MITSUBISHI (EU) GALANT VI GALANT 1.6 (1987-1990)



HYDRAULISK KOBLINGSSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

SERVOSTYRING

Kapacitet: 0,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

SMØREPUNKTER/NIPLER HJULLEJER BAG

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Multi Purpose Grease 3

Skift alle 60000 km/ 72 måneder

KØLESYSTEM

Kapacitet: 5,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Skift alle 40000 km/ 48 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.