

MITSUBISHI (EU) LANCER CY0 LANCER 1.8 DI-D CLEARTEC (110 KW) (2008-2016)



MOTOR 4N13

Kapacitet: 5,3 liter, Filterkapacitet: 0,3 liter

ANVEND

Foretrukne

KLIMA

Moderat

PRODUKTANBEFALING 1

Avanza MSP 0W-30

Skift alle 15000 km/ 12 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Presteza MSP 0W-30

PRODUKTANBEFALING 2

Helar SP LL-03 0W-30

PRODUKTANBEFALING 3

Avanza MSP 0W-30

Skift alle 15000 km/ 12 måneder

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

Presteza MSP 0W-30

PRODUKTANBEFALING 2

Helar SP LL-03 0W-30

PRODUKTANBEFALING 3

Avanza MSP 0W-30

Skift alle 7500 km

TRANSAKSEL MANUEL F5MBB 5/1

Kapacitet: 2,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

Kontroller alle 15000 km/ 12 måneder, skift alle 195000 km

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

Kontroller alle 15000 km/ 12 måneder, skift alle 90000 km

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Kontroller alle 15000 km/ 12 måneder, skift alle 30000 km/ 24 måneder

MITSUBISHI (EU) LANCER CY0 LANCER 1.8 DI-D CLEARTEC (110 KW) (2008-2016)



HYDRAULISK KOBLINGSSYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Kontroller alle 15000 km/ 12 måneder, skift alle 30000 km/ 24 måneder

SERVOSTYRING

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2032

PRODUKTANBEFALING 2

ATF Almirol

PRODUKTANBEFALING 3

ATF Dexron II-D

KØLESYSTEM

Kapacitet: 7,5 liter, Kapacitet: 0,62 liter (Reservetank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 30000 km/ 24 måneder, skift alle 120000 km/ 72 måneder

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 30000 km/ 24 måneder, skift alle 180000 km/ 108 måneder

KLIMAANLÆGSSYSTEM

Kapacitet: 480-520 gram

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.