

# MITSUBISHI (EU) LANCER CY0 LANCER 2.0 2WD (2008-2011)



## MOTOR 4B11

Kapacitet: 4,3 liter, Filterkapacitet: 0,3 liter

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

PRODUKTANBEFALING 1

**Bi-Turbo 20W-50**

Skift alle 20000 km/ 12 måneder

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Presteza MSP 0W-20**

PRODUKTANBEFALING 2

**Presteza MSP 0W-30**

PRODUKTANBEFALING 3

**Avanza MSP 0W-30**

Skift alle 20000 km/ 12 måneder

| ANVEND   | KLIMA            |
|----------|------------------|
| Krævende | Middelhavsagtigt |

PRODUKTANBEFALING 1

**Bi-Turbo 20W-50**

Skift alle 10000 km

| ANVEND   | KLIMA   |
|----------|---------|
| Krævende | Moderat |

PRODUKTANBEFALING 1

**Presteza MSP 0W-20**

PRODUKTANBEFALING 2

**Presteza MSP 0W-30**

PRODUKTANBEFALING 3

**Avanza MSP 0W-30**

Skift alle 10000 km

## TRANSAKSEL CVT F1CJA 1/1

Kapacitet: 7,1 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**SP Matic 4016**

Kontroller alle 20000 km/ 12 måneder, skift alle 80000 km

| ANVEND   | KLIMA   |
|----------|---------|
| Krævende | Moderat |

PRODUKTANBEFALING 1

**SP Matic 4016**

Kontroller alle 20000 km/ 12 måneder, skift alle 40000 km

# MITSUBISHI (EU) LANCER CY0 LANCER 2.0 2WD (2008-2011)



## TRANSAKSEL MANUEL F5MBB 5/1

Kapacitet: 2,5 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 |  |  |
|---------------------|--|--|
| <b>SP Gear 5015</b> |  |  |

Kontroller alle 20000 km/ 12 måneder, skift alle 200000 km

| ANVEND   | KLIMA   |
|----------|---------|
| Krævende | Moderat |

| PRODUKTANBEFALING 1 |  |  |
|---------------------|--|--|
| <b>SP Gear 5015</b> |  |  |

Kontroller alle 20000 km/ 12 måneder, skift alle 100000 km

## HYDRAULISK BREMSESYSYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2       | PRODUKTANBEFALING 3     |
|----------------------------------|---------------------------|-------------------------|
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> | <b>Drauliquid DOT 3</b> |

Kontroller alle 20000 km/ 12 måneder, skift alle 40000 km/ 24 måneder

## HYDRAULISK KOBLINGSSYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2       | PRODUKTANBEFALING 3     |
|----------------------------------|---------------------------|-------------------------|
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> | <b>Drauliquid DOT 3</b> |

Kontroller alle 20000 km/ 12 måneder, skift alle 40000 km/ 24 måneder

## SERVOSTYRING

Kapacitet: 1 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2 | PRODUKTANBEFALING 3    |
|----------------------|---------------------|------------------------|
| <b>SP Matic 2032</b> | <b>ATF Almirol</b>  | <b>ATF Dexron II-D</b> |

# MITSUBISHI (EU) LANCER CY0 LANCER 2.0 2WD (2008-2011)



## KØLESYSTEM

Kapacitet: 7 liter, Kapacitet: 0,65 liter (Reservetank)

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Coolant SP 14+**

*Kontroller alle 20000 km/ 12 måneder, skift alle 120000 km/ 72 måneder*

### ANVEND

Første skift kun

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Coolant SP 14+**

*Kontroller alle 20000 km/ 12 måneder, skift alle 180000 km/ 108 måneder*

## KLIMAANLÆGSSYSTEM

Kapacitet: 480-520 gram

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*