

MITSUBISHI (EU) SIGMA SIGMA 3.0 24V (1991-1996)



MOTOR Mitsubishi 6G72
Kapacitet: 4 liter, Filterkapacitet: 0,3 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Bi-Turbo 20W-50		

Skift alle 10000 km/ 6 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Emperol 5W-40	Asyntho 5W-30	Emperol 10W-40

Skift alle 10000 km/ 6 måneder

ANVEND	KLIMA
Krævende	Middelhavsagtigt

PRODUKTANBEFALING 1		
Bi-Turbo 20W-50		

Skift alle 5000 km

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Emperol 5W-40	Asyntho 5W-30	Emperol 10W-40

Skift alle 5000 km

TRANSAKSEL AUTOMATISK 4/1
Kapacitet: 7,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 4026		

Kontroller alle 20000 km, skift alle 40000 km/ 24 måneder

TRANSAKSEL MANUEL 5/1
Kapacitet: 2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 5015	Syngear 75W-90	Gearlube GL-4 80W

Kontroller alle 20000 km, skift alle 40000 km/ 24 måneder

MITSUBISHI (EU) SIGMA SIGMA 3.0 24V (1991-1996)



HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Drauliquid DOT 3		

Kontroller alle 40000 km, skift alle 80000 km/ 24 måneder

SERVOSTYRING

Kapacitet: 0,9 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
ATF Dexron II-D		

Kontroller alle 20000 km, skift alle 40000 km/ 24 måneder

SMØREPUNKTER/NIPLER HJULLEJER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Kontroller alle 20000 km/ 12 måneder

SMØREPUNKTER/NIPLER KUGLELED

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Kontroller alle 20000 km/ 12 måneder

KØLESYSTEM

Kapacitet: 8 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant -38 Organic NF		

Skift alle 50000 km/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.