

MITSUBISHI (EU) SPACE RUNNER SPACE RUNNER 2.0 16V (1999-2002)



MOTOR 4G63

Kapacitet: 4,3 liter, Kapacitet: 0,1 liter (Oliekøler), Filterkapacitet: 0,3 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 15000 km/ 12 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Avanza MSP 0W-30

PRODUKTANBEFALING 2

Duranza LSP 5W-30

PRODUKTANBEFALING 3

Helar 0W-40

Skift alle 15000 km/ 12 måneder

TRANSAKSEL AUTOMATISK F4A42, Invecs II 4A/T 4/1

Kapacitet: 7,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Kontroller alle 15000 km/ 12 måneder, skift alle 90000 km/ 72 måneder

TRANSAKSEL MANUEL F5M42 5/1

Kapacitet: 2,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Syngear TDL 75W-90

Kontroller alle 15000 km/ 12 måneder, skift alle 105000 km/ 84 måneder

HYDRAULISK BREMSE-/KOPLINGSSYSTEM ABS

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Kontroller alle 15000 km/ 12 måneder, skift alle 30000 km/ 24 måneder

MITSUBISHI (EU) SPACE RUNNER SPACE RUNNER 2.0 16V (1999-2002)



SERVOSTYRING

Kapacitet: 0,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 15000 km/ 12 måneder

KØLESYSTEM

Kapacitet: 6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Kontroller alle 30000 km/ 24 måneder, skift alle 60000 km/ 48 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.