

MITSUBISHI (EU) SPACE STAR / MIRAGE A0 SPACE STAR / MIRAGE 1.0 MIVEC (2012-2018)



MOTOR 3A90

Kapacitet: 3 liter, Filterkapacitet: 0,2 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 20000 km/ 12 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Presteza MSP 0W-20

PRODUKTANBEFALING 2

Presteza MSP 0W-30

PRODUKTANBEFALING 3

Avanza MSP 0W-30

Skift alle 20000 km/ 12 måneder

ANVEND	KLIMA
Krævende	Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 10000 km

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1

Presteza MSP 0W-20

PRODUKTANBEFALING 2

Presteza MSP 0W-30

PRODUKTANBEFALING 3

Avanza MSP 0W-30

Skift alle 10000 km

TRANSAKSEL CVT F1CJB 1/1

Kapacitet: 7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Matic 4016

Kontroller alle 20000 km/ 12 måneder, skift alle 80000 km

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1

SP Matic 4016

Kontroller alle 20000 km/ 12 måneder, skift alle 40000 km

MITSUBISHI (EU) SPACE STAR / MIRAGE

A0 SPACE STAR / MIRAGE 1.0 MIVEC (2012-2018)



TRANSAXSEL MANUEL F5MBD 5/1

Kapacitet: 1,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Gear 5015		

Kontroller alle 20000 km/ 12 måneder, skift alle 200000 km

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1		
SP Gear 5015		

Kontroller alle 20000 km/ 12 måneder, skift alle 100000 km

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Kontroller alle 20000 km/ 12 måneder, skift alle 40000 km/ 24 måneder

KØLESYSTEM

Kapacitet: 4,6 liter (med CVT), Kapacitet: 4 liter (med manuel transaksel)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Coolant SP 14+		

Kontroller alle 40000 km/ 24 måneder, skift alle 120000 km/ 72 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Coolant SP 14+		

Kontroller alle 40000 km/ 24 måneder, skift alle 200000 km/ 120 måneder

KLIMAANLÆGSSYSTEM R-1234yf

Kapacitet: 250-290 gram

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.