

MITSUBISHI (EU) STARION STARION 2.0 TURBO (1984-1986)



MOTOR 4G63T

Kapacitet: 3,5 liter, Filterkapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Emperol 10W-40

PRODUKTANBEFALING 2

Classic Racing Oil 15W-50

PRODUKTANBEFALING 3

Bi-Turbo 15W-40

Skift alle 5000 km/ 6 måneder

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Asyntho 5W-30

Skift alle 5000 km/ 6 måneder

DIFFERENTIALE BAG

Kapacitet: 1,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

Kontroller alle 20000 km/ 24 måneder, skift alle 80000 km/ 96 måneder

GEAR MANUEL 5/1

Kapacitet: 2,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Syngear 75W-90

PRODUKTANBEFALING 3

Gearlube GL-4 80W

Kontroller alle 20000 km/ 24 måneder, skift alle 40000 km/ 48 måneder

SELVSPÆRRENDE DIFFERENTIALE BAG

Kapacitet: 1,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Skift alle 20000 km/ 24 måneder

MITSUBISHI (EU) STARION STARION 2.0 TURBO (1984-1986)



HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Skift alle 40000 km/ 48 måneder

SERVOSTYRING

Kapacitet: 0,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 10000 km/ 12 måneder

KØLESYSTEM

Kapacitet: 7,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Kontroller alle 10000 km/ 12 måneder, skift alle 40000 km/ 24 måneder

STYRETØJ

Kapacitet: 0,28 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Gearlube GL-5 80W-90

Kontroller alle 20000 km/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.