MITSUBISHI (EU) ASX / RVR GA0 ASX / RVR 1.8 DI-D 2WD (85 KW) (2010-2014)



Capacity: 5,3 liter, Filter capacity: 0,3 liter USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza MSP 0W-30	Presteza MSP 0W-30	Helar SP LL-03 0W-30
Change every 15000 km/ 12 montl	hs	
USE		CLIMATE
Severe		Moderate
	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
PRODUCT RECOMMENDATION 1		

TRANSAXLE MANUAL F6MBA 6/1 Capacity: 2,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		
Check every 15000 km/ 12 months, chang	ge every 195000 km	
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		
Check every 15000 km/ 12 months, change	ge every 90000 km	

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3		
Check every 15000 km/ 12 months, cha	inge every 30000 km/ 24 months	'		

MITSUBISHI (EU) ASX / RVR GA0 ASX / RVR 1.8 DI-D 2WD (85 KW) (2010-2014)



01 1 150001 /10 11 1	000001 /04 //	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.)		

Check every 15000 km/12 months, change every 30000 km/24 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Check every 30000 km/24 months, cha	nge every 120000 km/ 72 months	
USE		CLIMATE
First change only		Moderate

Check every 30000 km/24 months, change every 180000 km/108 months

AIRCONDITIONING COMPRESSOR

Capacity: 70-90 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 480-520 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.