## MITSUBISHI (EU) COLT CZ3/5 COLT 1.1 (2004-2007)



| <b>ENGINE</b> 134910<br>Capacity: 3,2 liter, Filter capacity: 0,2 liter |                               |                          |
|---|-------------------------------|--------------------------|
| USE   |                               | CLIMATE                  |
| Normal  |                               | Mediterranean            |
| PRODUCT RECOMMENDATION 1  |                               |                          |
| Bi-Turbo 20W-50   |                               |                          |
| Change every 20000 km/ 12 months  |                               |                          |
| USE   |                               | CLIMATE                  |
| Normal  |                               | Moderate                 |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3 |
| Helar 0W-40   | Emperol 5W-40                 | Emperol 10W-40           |
| Change every 20000 km/ 12 months  |                               |                          |
| USE   |                               | CLIMATE                  |
| Severe  |                               | Mediterranean            |
| PRODUCT RECOMMENDATION 1  |                               |                          |
| Bi-Turbo 20W-50   |                               |                          |
| Change every 10000 km   |                               |                          |
| USE   |                               | CLIMATE                  |
| Severe  |                               | Moderate                 |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3 |
| Helar 0W-40   | Emperol 5W-40                 | Emperol 10W-40           |
| Change every 10000 km   |                               |                          |
| TRANSAXLE MANUAL F5MGA 5/1  |                               |                          |
| Capacity: 1,75 liter  |                               |                          |
| USE   |                               | CLIMATE                  |
| Normal  |                               | Moderate                 |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011  | Syngear TDL 75W-90            | Syngear 75W-90           |
| Check every 20000 km/ 12 months, change                                 | e every 200000 km/ 120 months |                          |

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Severe                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011             | Syngear TDL 75W-90       | Syngear 75W-90           |

Check every 20000 km/ 12 months, change every 100000 km/ 60 months

## MITSUBISHI (EU) COLT CZ3/5 COLT 1.1 (2004-2007)



| HYDRAULIC BRAKE/CLUTCH SYSTEM ABS |                          |          |  |  |
|-----------------------------------|--------------------------|----------|--|--|
| USE                               |                          | CLIMATE  |  |  |
| Normal                            |                          | Moderate |  |  |
| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2 |          |  |  |
| Drauliquid-LV Super DOT 4         | Drauliquid-S DOT 4       |          |  |  |

Check every 20000 km/ 12 months, change every 40000 km/ 24 months

| COOLING SYSTEM<br>Capacity: 4,2 liter |          |
|---------------------------------------|----------|
| USE                                   | CLIMATE  |
| Normal                                | Moderate |
| PRODUCT RECOMMENDATION 1              |          |
| Coolant -38 Organic NF                |          |
|                                       |          |

Check every 40000 km/24 months, change every 60000 km/48 months

## AIRCONDITIONING COMPRESSOR Capacity: 100 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.