

# MITSUBISHI (EU) GALANT VI GALANT 2.0i 4WD (1990-1993)

**ENGINE 4G63-SOHC**

Capacity: 3,9 liter, Filter capacity: 0,4 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 15000 km/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Emperol 5W-40**

## PRODUCT RECOMMENDATION 2

**Asyntho 5W-30**

## PRODUCT RECOMMENDATION 3

**Emperol 10W-40***Change every 15000 km/ 12 months***DIFFERENTIAL REAR (4x4)**

Capacity: 0,7 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90***Check every 30000 km/ 24 months, change every 90000 km/ 72 months***TRANSAXLE MANUAL 5/1**

Capacity: 2,2 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**SP Gear 5015**

## PRODUCT RECOMMENDATION 2

**Syngear 75W-90***Check every 15000 km/ 12 months, change every 75000 km/ 60 months*

# MITSUBISHI (EU) GALANT VI GALANT 2.0I 4WD (1990-1993)

**TRANSFERBOX**

Capacity: 0,6 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Gear 5015</b>      | <b>Syngear 75W-90</b>    |          |

Check every 15000 km/ 12 months, change every 45000 km/ 36 months

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Severe                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Gear 5015</b>      | <b>Syngear 75W-90</b>    |          |

Change every 15000 km/ 12 months

**HYDRAULIC BRAKE SYSTEM**

Capacity: 0,6 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Drauliquid DOT 3</b>  |  |          |

Change every 30000 km/ 24 months

**HYDRAULIC CLUTCH SYSTEM**

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Drauliquid DOT 3</b>  |  |          |

**POWER STEERING**

Capacity: 0,9 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>ATF Dexron II-D</b>   |  |          |

# MITSUBISHI (EU) GALANT VI GALANT 2.0I 4WD (1990-1993)

**COOLING SYSTEM**

Capacity: 6,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF***Change every 60000 km/ 48 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*