

MITSUBISHI (EU) PAJERO PININ / SHOGUN PININ PAJERO PININ / SHOGUN PININ 2.0 GDI (2001-2005)

**ENGINE 4G94**

Capacity: 3,8 liter, Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Change every 15000 km/ 12 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Change every 7500 km***DIFFERENTIAL FRONT**

Capacity: 0,83 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Check every 30000 km/ 24 months, change every 90000 km/ 72 months*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

PRODUCT RECOMMENDATION 3

SP Gear 1071*Check every 30000 km/ 24 months, change every 90000 km/ 72 months***DIFFERENTIAL REAR**

Capacity: 1,7 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Check every 30000 km/ 24 months, change every 90000 km/ 72 months*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

PRODUCT RECOMMENDATION 3

SP Gear 1071*Check every 30000 km/ 24 months, change every 90000 km/ 72 months*

MITSUBISHI (EU) PAJERO PININ / SHOGUN PININ PAJERO PININ / SHOGUN PININ 2.0 GDI (2001-2005)

**TRANSFERBOX**

Capacity: 2,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Syngear TDL 75W-90

Check every 15000 km/ 12 months, change every 45000 km/ 36 months

TRANSMISSION AUTOMATIC 4/1

Capacity: 7,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 15000 km/ 12 months, change every 45000 km/ 36 months

TRANSMISSION MANUAL 5/1

Capacity: 2,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Syngear TDL 75W-90

Check every 15000 km/ 12 months, change every 45000 km/ 36 months

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 15000 km/ 12 months, change every 30000 km/ 24 months

MITSUBISHI (EU) PAJERO PININ / SHOGUN PININ PAJERO PININ / SHOGUN PININ 2.0 GDI (2001-2005)

**OVERRUNNING CLUTCH FRONT**

Capacity: 0,12 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		

Check every 30000 km/ 24 months, change every 90000 km/ 72 months

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Gearlube RPC 75W-80	SP Gear 1071

Check every 30000 km/ 24 months, change every 90000 km/ 72 months

POWER STEERING

Capacity: 0,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 15000 km/ 12 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 24 months/ 30000 km

COOLING SYSTEM

Capacity: 6 liter

USE		CLIMATE
Normal		All climates
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Check every 30000 km/ 24 months, change every 60000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.