

NISSAN (EU) ALMERA ALMERA 1.8i (2000-2002)



ENGINE QG18DE
Capacity: 2,7 liter, Filter capacity: 0,2 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50

Change every 15000 km/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Emperol 10W-40

PRODUCT RECOMMENDATION 3

Bi-Turbo 15W-40

Change every 15000 km/ 12 months

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Duranza LSP 5W-30

Change every 15000 km/ 12 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Duranza ECO 5W-20

Change every 15000 km/ 12 months

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50

Change every 7500 km/ 6 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Emperol 10W-40

PRODUCT RECOMMENDATION 3

Bi-Turbo 15W-40

Change every 7500 km/ 6 months

USE	CLIMATE
Severe	Cold

PRODUCT RECOMMENDATION 1

Duranza LSP 5W-30

Change every 7500 km/ 6 months

NISSAN (EU) ALMERA ALMERA 1.8i (2000-2002)



USE		CLIMATE
Severe		Arctic
PRODUCT RECOMMENDATION 1		
Duranza ECO 5W-20		
Change every 7500 km/ 6 months		

TRANSAXLE AUTOMATIC 4/1 Capacity: 7,7 liter		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4026	SP Matic 2032	
Change every 30000 km/ 24 months		

USE		CLIMATE
<30.000 km/1 year		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4026	SP Matic 2032	
Check every 15000 km/ 12 months		

USE		CLIMATE
>30.000 km/1 year		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4026	SP Matic 2032	
Check every 24 months/ 30000 km		

TRANSAXLE MANUAL RS5F70A 5/1 Capacity: 3 liter		
USE		CLIMATE
<30.000 km/1 year		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		
Check every 15000 km/ 12 months		

USE		CLIMATE
>30.000 km/1 year		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		
Check every 24 months/ 30000 km		

NISSAN (EU) ALMERA ALMERA 1.8i (2000-2002)



HYDRAULIC BRAKE/CLUTCH SYSTEM ABS AS OPTION

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 15000 km/ 12 months, change every 30000 km/ 24 months

POWER STEERING

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 15000 km/ 12 months

COOLING SYSTEM

Capacity: 6,6-6,7 liter, Capacity: 0,7 liter (Reservoir)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 16	Coolant SP 14+	

Check every 15000 km/ 12 months, change every 60000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.