

# NISSAN (EU) ALMERA ALMERA 1.8i (2002-2006)

**ENGINE QG18DE**

Capacity: 3 liter (Dry fill), Capacity: 2,9 liter (Service fill), Filter capacity: 0,2 liter

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Asyntho 5W-30</b>     | <b>Emperol 10W-40</b>    | <b>Bi-Turbo 15W-40</b>   |

*Change every 15000 km/ 12 months*

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Severe                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Asyntho 5W-30</b>     | <b>Emperol 10W-40</b>    | <b>Bi-Turbo 15W-40</b>   |

*Change every 7500 km/ 6 months***TRANSAXLE AUTOMATIC 4/1**

Capacity: 7,7 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Severe                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Matic 4026</b>     | <b>SP Matic 2032</b>     |          |

*Change every 30000 km/ 24 months*

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| <30.000 km/1 year        |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Matic 4026</b>     | <b>SP Matic 2032</b>     |          |

*Check every 15000 km/ 12 months*

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| >30.000 km/1 year        |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Matic 4026</b>     | <b>SP Matic 2032</b>     |          |

*Check every 24 months/ 30000 km*

# NISSAN (EU) ALMERA ALMERA 1.8i (2002-2006)



## TRANSAXLE MANUAL RS5F70A 5/1

Capacity: 3 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| <30.000 km/1 year        |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Gear 5015</b>      |  |          |

Check every 15000 km/ 12 months

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| >30.000 km/1 year        |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Gear 5015</b>      |  |          |

Check every 24 months/ 30000 km

## HYDRAULIC BRAKE/CLUTCH SYSTEM ABS AS OPTION

| USE                              |                           | CLIMATE                  |
|----------------------------------|---------------------------|--------------------------|
| Normal                           |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> | <b>Drauliquid DOT 3</b>  |

Check every 15000 km/ 12 months, change every 30000 km/ 24 months

## POWER STEERING

Capacity: 1 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       |          |

Check every 15000 km/ 12 months

## COOLING SYSTEM

Capacity: 6,6-6,7 liter, Capacity: 0,7 liter (Reservoir)

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant SP 16</b>     | <b>Coolant SP 14+</b>    |          |

Check every 15000 km/ 12 months, change every 60000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.