

NISSAN (EU) PATROL Y61 PATROL 4.8 (206 KW) (2007-2010)



ENGINE TB48DE
Capacity: 6,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza LSP 5W-30	Asyntho 5W-30	Emperol 10W-40

Change every 10000 km/ 6 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza LSP 5W-30	Asyntho 5W-30	Emperol 10W-40

Change every 5000 km/ 3 months

DIFFERENTIAL FRONT H233B
Capacity: 5,4 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		

Check every 20000 km/ 12 months, change every 60000 km/ 36 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Gearlube RPC 75W-80

Check every 20000 km/ 12 months, change every 60000 km/ 36 months

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
SP Gear 1081		

Check every 20000 km/ 12 months, change every 60000 km/ 36 months

NISSAN (EU) PATROL Y61 PATROL 4.8 (206 KW) (2007-2010)


DIFFERENTIAL REAR H233B

Capacity: 2,1 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gearlube GL-5 85W-140*Check every 20000 km/ 12 months, change every 60000 km/ 36 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

SP Gear 5015

PRODUCT RECOMMENDATION 3

Gearlube RPC 75W-80*Check every 20000 km/ 12 months, change every 60000 km/ 36 months*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

SP Gear 1081*Check every 20000 km/ 12 months, change every 60000 km/ 36 months*
DIFFERENTIAL REAR LIMITED SLIP H233B

Capacity: 2,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140*Check every 20000 km/ 12 months, change every 60000 km/ 36 months*

NISSAN (EU) PATROL Y61 PATROL 4.8 (206 KW) (2007-2010)


DIFFERENTIAL REAR WITH DIFFERENTIAL LOCK H233B

Capacity: 3 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gearlube GL-5 85W-140

Check every 20000 km/ 12 months, change every 60000 km/ 36 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

SP Gear 5015

PRODUCT RECOMMENDATION 3

Gearlube RPC 75W-80

Check every 20000 km/ 12 months, change every 60000 km/ 36 months

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

SP Gear 1081

Check every 20000 km/ 12 months, change every 60000 km/ 36 months

TRANSFERBOX TX12A

Capacity: 1,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Syngear 75W-90

Check every 20000 km/ 12 months, change every 60000 km/ 36 months

TRANSMISSION AUTOMATIC RE5R05A 5/1

Capacity: 10,4-10,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

Check every 12 months/ 30000 km

NISSAN (EU) PATROL Y61 PATROL 4.8 (206 KW) (2007-2010)



TRANSMISSION MANUAL FS5R50B 5/1

Capacity: 3,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90

Change every 80000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Change every 40000 km/ 48 months

POWER STEERING

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 20000 km/ 12 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 20000 km/ 12 months

COOLING SYSTEM

Capacity: 13 liter, Capacity: 13,9 liter (+ rear heater), Capacity: 12,5 liter (Without heater)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Change every 60000 km/ 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.