

NISSAN (EU) SUNNY SUNNY 1.6i AWD N14 (1991-1995)



MOTOR GA16DE

Kapacitet: 3,2 liter, Filterkapacitet: 0,4 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 15000 km/ 6 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Emperol 10W-40

PRODUKTANBEFALING 2

Classic Racing Oil 15W-50

PRODUKTANBEFALING 3

Bi-Turbo 15W-40

Skift alle 15000 km/ 6 måneder

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1

Asyntho 5W-30

Skift alle 15000 km/ 6 måneder

DIFFERENTIALE BAG (4x4)

Kapacitet: 1 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

Kontroller alle 12 måneder/ 30000 km

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Gearlube RPC 75W-80

Kontroller alle 12 måneder/ 30000 km

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1

SP Gear 1081

Kontroller alle 12 måneder/ 30000 km

NISSAN (EU) SUNNY SUNNY 1.6i AWD N14 (1991-1995)



REDUKTIONSGEARKASSE

Kapacitet: 1,1 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

Kontroller alle 12 måneder/ 30000 km

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Gearlube RPC 75W-80

Kontroller alle 12 måneder/ 30000 km

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1

SP Gear 1081

Kontroller alle 12 måneder/ 30000 km

TRANSAKSEL AUTOMATISK 3/1

Kapacitet: 7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Matic 2032

Kontroller alle 15000 km/ 6 måneder

TRANSAKSEL MANUEL 5/1

Kapacitet: 2,9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Syngear TDL 75W-90

Kontroller alle 15000 km/ 6 måneder

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1

SP Gear 1081

Kontroller alle 15000 km/ 6 måneder

NISSAN (EU) SUNNY SUNNY 1.6i AWD N14 (1991-1995)



HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Kontroller alle 15000 km/ 6 måneder, skift alle 30000 km/ 12 måneder

HYDRAULISK KOBLINGSSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Kontroller alle 15000 km/ 6 måneder

SERVOSTYRING

Kapacitet: 0,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2032

Kontroller alle 15000 km/ 6 måneder

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Kontroller alle 12 måneder/ 30000 km

KØLESYSTEM

Kapacitet: 5,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Kontroller alle 30000 km/ 12 måneder, skift alle 60000 km/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.