

NISSAN (USA / CAN) SENTRA B16 SENTRA 2.5 (USA) (2009-2010)

**ENGINE QR25DE**

Capacity: 5,1 liter (Dry fill), Capacity: 4,3 liter (Service fill), Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Presteza MSP 5W-30	Armado Synth LSP Ultra 5W-30

Change every 7500 miles/ 6 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Presteza MSP 5W-30	Armado Synth LSP Ultra 5W-30

*Change every 3750 miles/ 3 months***TRANSMISSION CVT**

Capacity: 7,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
SP Matic 4016	

Check every 15000 miles/ 12 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	
SP Matic 4016	

*Change every 60000 miles***TRANSMISSION MANUAL**

Capacity: 1,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
SP Gear 5015	

Check every 15000 miles/ 12 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	
SP Gear 5015	

Change every 30000 miles/ 24 months

NISSAN (USA / CAN) SENTRA B16 SENTRA 2.5 (USA) (2009-2010)



HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 15000 miles/ 12 months*

HYDRAULIC CLUTCH SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 15000 miles/ 12 months*

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 7,1 liter (+ automatic transmission/transaxle), Capacity: 6,9 liter (+ manual transmission/transaxle)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+*Change every 30000 miles/ 24 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+*Change every 60000 miles/ 48 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.