

NISSAN (USA / CAN) SENTRA B16 SENTRA 2.5 (USA) (2012-2013)



MOTOR QR25DE

Kapacitet: 4,3 liter (Servicepåfyldning), Kapacitet: 5,1 liter (Tør efterfyld), Filterkapacitet: 0,3 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Presteza MSP 5W-30	Armado Synth LSP Ultra 5W-30

Skift alle 7500 mil/ 6 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Presteza MSP 5W-30	Armado Synth LSP Ultra 5W-30

Skift alle 3750 mil/ 3 måneder

GEAR CVT

Kapacitet: 7,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	
SP Matic 4016	

Kontroller alle 15000 mil/ 12 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	
SP Matic 4016	

Skift alle 60000 mil

GEAR MANUEL

Kapacitet: 1,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
SP Gear 5015	Syngear 75W-90

Kontroller alle 15000 mil/ 12 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
SP Gear 5015	Syngear 75W-90

Skift alle 30000 mil/ 24 måneder

NISSAN (USA / CAN) SENTRA B16 SENTRA 2.5 (USA) (2012-2013)



HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Kontroller alle 15000 mil/ 12 måneder

HYDRAULISK KOBLINGSSYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Kontroller alle 15000 mil/ 12 måneder

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 7,1 liter (+ automatisk transmission/transaksel), Kapacitet: 6,9 liter (+ manuel transmission/transaksel)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Skift alle 75000 mil/ 60 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Skift alle 105000 mil/ 84 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.