

# NISSAN (USA / CAN) GT-R R35 GT-R (USA) (2012-2016)

**ENGINE VR38DETT**

Capacity: 6,2 liter (Dry fill), Capacity: 5 liter (Service fill), Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Helar 0W-40***Change every 6000 miles/ 6 months***FINAL DRIVE FRONT F160A**

Capacity: 0,65 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube Racing 75W-140***Check every 12000 miles/ 12 months, change every 36000 miles/ 36 months***FINAL DRIVE REAR**

Capacity: 1,35 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube Racing 75W-140***Check every 12000 miles/ 12 months, change every 36000 miles/ 36 months***TRANSMISSION MANUAL GR6Z30A 6/1**

Capacity: 9,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2072***Check every 12000 miles/ 12 months, change every 36000 miles/ 36 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid Racing***Check every 12000 miles/ 12 months, change every 24000 miles/ 24 months*

# NISSAN (USA / CAN) GT-R R35 GT-R (USA) (2012-2016)



## POWER STEERING

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 4036***Check every 6000 miles/ 6 months*

## GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2**

## COOLING SYSTEM

Capacity: 11,3 liter, Capacity: 1,4 liter (Reservoir)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 14+***Change every 24000 miles/ 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.