NISSAN (USA / CAN) MAXIMA A34 MAXIMA 3.5 (USA) (2006-2007)



ENGINE VQ35DE Capacity: 4,6 liter (Dry fill), Capacity: 4,2 liter (Service fill), Filter capacity: 0,2 liter				
use Normal		CLIMATE		
		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Presteza MSP 5W-30	Asyntho 5W-30	Emperol 10W-40		
Change every 7500 miles/ 6 months				
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Presteza MSP 5W-30	Asyntho 5W-30	Emperol 10W-40		
Change every 3750 miles/ 3 months				

TRANSMISSION CVT RE0F09B 1/1 Capacity: 10 liter				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
SP Matic 4016				
Check every 15000 miles/ 12 months				
USE	CLIMATE			
Severe	Moderate			
PRODUCT RECOMMENDATION 1				
SP Matic 4016				

HYDRAULIC BRAKE SYSTEM				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
Drauliquid DOT 3				
Check every 15000 miles/ 12 months				

Change every 60000 miles

NISSAN (USA / CAN) MAXIMA A34 MAXIMA 3.5 (USA) (2006-2007)



POWER STEERING Capacity: 1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2032	

GREASE POINTS/NIPPLES				
use Normal		CLIMATE		
		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		

COOLING SYSTEM Capacity: 8,5 liter (Total)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant SP 14+			
Change every 30000 miles/24 months			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant SP 14+			
Change every 60000 miles/ 48 months			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.