NISSAN (USA / CAN) SENTRA B14 SENTRA 1.8 (USA) (1998-1998)



ENGINE QG18DE Capacity: 3,2 liter (Service fill), Filter capacity: 0,4 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Asyntho 5W-30	Emperol 10W-40		
Change every 7500 miles/ 6 months			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Asyntho 5W-30	Emperol 10W-40		

Change every 3750 miles/ 3 months

TRANSAXLE AUTOMATIC Capacity: 7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4026	
Check every 15000 miles/ 12 months	

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Change even 20000 miles 24 months		

Change every 30000 miles/24 months

TRANSMISSION MANUAL Capacity: 2,9-3,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube GL-4 80W-90	

Check every 15000 miles/ 12 months

USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube GL-4 80W-90	
Change every 30000 miles/24 months	· ·

NISSAN (USA / CAN) SENTRA B14 SENTRA 1.8 (USA) (1998-1998)



HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Chack over 15000 miles / 12 months		

Check every 15000 miles/ 12 months

POWER STEERING Capacity: 0-0 liter (Between min and max.)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Almirol		
Check even 20000 miles (24 mentes			

Check every 30000 miles/ 24 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	
Check every 7500 miles/ 6 months		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 5,7 liter (+ automatic transmission/transaxle), Capacity: 5,2 liter (+ manual transmission/transaxle)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant SP 14+			
Change every 30000 miles/24 months			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.