

# OPEL ASTRA F CABRIO T92 ASTRA F CABRIO 1.8 (1994-2000)



**MOTOR** C18XEL, X18XE  
Kapacitet: 4 liter

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1    |  |  |
|------------------------|--|--|
| <b>Bi-Turbo 20W-50</b> |  |  |

Skift alle 15000 km/ 12 måneder

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2  | PRODUKTANBEFALING 3          |
|---------------------|----------------------|------------------------------|
| <b>Helar 0W-40</b>  | <b>Emperol 5W-40</b> | <b>Emperol Racing 10W-60</b> |

Skift alle 15000 km/ 12 måneder

| ANVEND   | KLIMA            |
|----------|------------------|
| Krævende | Middelhavsagtigt |

| PRODUKTANBEFALING 1    |  |  |
|------------------------|--|--|
| <b>Bi-Turbo 20W-50</b> |  |  |

Skift alle 15000 km/ 6 måneder

| ANVEND   | KLIMA   |
|----------|---------|
| Krævende | Moderat |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2  | PRODUKTANBEFALING 3          |
|---------------------|----------------------|------------------------------|
| <b>Helar 0W-40</b>  | <b>Emperol 5W-40</b> | <b>Emperol Racing 10W-60</b> |

Skift alle 15000 km/ 6 måneder

**TRANSAKSEL MANUEL F18 5/1**  
Kapacitet: 1,8 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2      |  |
|---------------------|--------------------------|--|
| <b>SP Gear 5015</b> | <b>Gearlube GL-4 80W</b> |  |

Kontroller alle 15000 km/ 12 måneder

## HYDRAULISK AKTIVERING KALECHE

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  |  |  |
|----------------------|--|--|
| <b>SP Fluid 3023</b> |  |  |

# OPEL ASTRA F CABRIO T92 ASTRA F CABRIO 1.8 (1994-2000)



## HYDRAULISK BREMSESYSTEM

| ANVEND                           |                           | KLIMA   |
|----------------------------------|---------------------------|---------|
| Normal                           |                           | Moderat |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2       |         |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |         |

*Skift alle 24 måneder*

## SERVOSTYRING

Kapacitet: 1 liter

| ANVEND                 |  | KLIMA   |
|------------------------|--|---------|
| Normal                 |  | Moderat |
| PRODUKTANBEFALING 1    |  |         |
| <b>ATF Dexron II-D</b> |  |         |

*Kontroller alle 24 måneder/ 30000 km*

## KØLESYSTEM

Kapacitet: 6,9 liter

| ANVEND               |  | KLIMA   |
|----------------------|--|---------|
| Normal               |  | Moderat |
| PRODUKTANBEFALING 1  |  |         |
| <b>Coolant SP 11</b> |  |         |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*