

OPEL ASTRA H A04 ASTRA H 1.3 CDTI (2004-2010)



MOTOR Z13DTH

Kapacitet: 3,1 liter, Filterkapacitet: 0,2 liter

ANVEND

Fleksibel (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

Presteza MSP 5W-30

PRODUKTANBEFALING 2

Helar MSP+ 5W-40

PRODUKTANBEFALING 3

Specialsynth MSP 5W-40

Skift alle 30000 km/ 12 måneder

TRANSAKSEL HALVAUTOMATISK M20 MTA 6/1

Kapacitet: 1,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Syngear TDL 75W-90

Kontroller alle 12 måneder/ 30000 km

TRANSAKSEL MANUEL M20 6/1

Kapacitet: 2,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Syngear TDL 75W-90

Kontroller alle 12 måneder/ 30000 km

HYDRAULISK AKTIVERING KOBLINGSMODUL MTA

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

Kontroller alle 30000 km/ 12 måneder, skift alle 24 måneder

HYDRAULISK AKTIVERING SKIFTEMODUL M20 MTA

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3023

Kontroller alle 12 måneder/ 30000 km

OPEL ASTRA H A04 ASTRA H 1.3 CDTI (2004-2010)



HYDRAULISK BREMSESYSTEM

Kapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

Kontroller alle 30000 km/ 12 måneder, skift alle 24 måneder

SERVOSTYRING

Kapacitet: 0,6-0,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

Kontroller alle 12 måneder/ 30000 km

KØLESYSTEM

Kapacitet: 7,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15

PRODUKTANBEFALING 2

Coolant SP 15+

Kontroller alle 12 måneder/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.