

# OPEL COMBO D TOUR X12 COMBO D TOUR 1.4 TURBO (2014-2018)



**ENGINE** 198A4000, A/B14FP  
Capacity: 2,7 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Helar SP LL-03 0W-30</b>	<b>Helar SP LL-03 5W-30</b>	<b>Presteza MSP 5W-30</b>

*Change every 30000 km/ 12 months*

**TRANSAXLE MANUAL** C635 6/1  
Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 1011</b>	<b>SP Gear 5015</b>	<b>Syngear TDL 75W-90</b>

## HYDRAULIC BRAKE/CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Drauliquid-LV Super DOT 4</b>		

*Check every 30000 km/ 12 months, change every 120000 km/ 48 months*

## POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Matic 4036</b>		

## COOLING SYSTEM

Capacity: 5,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15</b>	<b>Coolant SP 15+</b>	

*Check every 12 months/ 30000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.