OPEL INSIGNIA A G09 INSIGNIA A 2.8 V6 TURBO 4X4 (2008-2012)



ENGINE A28NET Capacity: 6,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Helar MSP+ 5W-40	Specialsynth MSP 5W-40

Change every 30000 km/ 12 months

DIFFERENTIAL REAR (4x4) Capacity: 0,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

TRANSAXLE AUTOMATIC AF 40 6/1 Capacity: 7 liter (Dry fill), Capacity: 3 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		
01		

Change every 80000 km/72 months

TRANSAXLE MANUAL F40 6/1 Capacity: 1,8 liter (Dry fill), Capacity	y: 1,6 liter (Service fill)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Syngear TDL 75W-90

TRANSFERBOX	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	

OPEL INSIGNIA A G09 INSIGNIA A 2.8 V6 TURBO 4X4 (2008-2012)



HALDEX-CLUTCH	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 6033	

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 60000 km/ 24 months	
USE	CLIMATE
First change only	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 30000 km/ 12 months	·

POWER STEERING Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Check every 12 months/ 30000 km	'

COOLING SYSTEM Capacity: 0-0 liter (Between min an	d max.)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15	Coolant SP 15+	
Check every 12 months/ 30000 km		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.