OPEL OMEGA A V87 OMEGA A 1.8I (1986-1993)



| USE CLIMATE Normal Mediterranean PRODUCT RECOMMENDATION 1 Image of the second seco | ENGINE 18SEH Capacity: 4,5 liter, Filter capacity: 0,25 liter | | |
|--|---|--------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 Change every 15000 km/ 12 months USE USE CLIMATE Normal PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Helar 0W-40 Emperol 5W-40 USE CLIMATE Severe Mediterranean PRODUCT RECOMMENDATION 1 Mediterranean Bi-Turbo 20W-50 CLIMATE Change every 15000 km/ 6 months CLIMATE Severe Mediterranean PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 Change every 15000 km/ 6 months CLIMATE Severe Mediterranean PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Bi-Turbo 20W-50 CLIMATE Change every 15000 km/ 6 months CLIMATE Severe Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 Emperol 5W-40 PRODUCT RECOMMENDATION 3 Emperol 5W-40 Emperol Racing 10W-60 Empero | USE | | CLIMATE |
| Bi-Turbo 20W-50 Image of the second | Normal | | Mediterranean |
| Change every 15000 km/ 12 months CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Helar 0W-40 Emperol 5W-40 Emperol Racing 10W-60 Change every 15000 km/ 12 months Emperol 5W-40 Emperol Racing 10W-60 Use CLIMATE Mediterranean Severe Mediterranean Mediterranean PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 CLIMATE Change every 15000 km/ 6 months CLIMATE Mediterranean VSE CLIMATE Mediterranean PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Bi-Turbo 20W-50 CLIMATE Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Biero Barter PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Helar 0W-40 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Emperol SW-40 | PRODUCT RECOMMENDATION 1 | | |
| USE Normal CLIMATE Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Emperol 5W-40 PRODUCT RECOMMENDATION 3 Emperol Racing 10W-60 Change every 15000 km/ 12 months Emperol 5W-40 Emperol Racing 10W-60 USE Severe CLIMATE Mediterranean PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 Mediterranean Change every 15000 km/ 6 months CLIMATE Mediterranean USE Severe CLIMATE Mediterranean PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 CLIMATE Mediterranean USE Severe CLIMATE Moderate PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 PRODUCT RECOMMENDATION 2 Emperol 5W-40 | Bi-Turbo 20W-50 | | |
| Normal Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Helar 0W-40 Emperol 5W-40 Emperol Racing 10W-60 Change every 15000 km/ 12 months CLIMATE VSE CLIMATE Severe Mediterranean PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 CLIMATE Change every 15000 km/ 6 months CLIMATE VSE CLIMATE Severe Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Bi-Turbo 20W-50 V Change every 15000 km/ 6 months V VSE CLIMATE Severe Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 PROPOL 5W-40 | Change every 15000 km/ 12 months | | |
| PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Helar 0W-40 Emperol 5W-40 Emperol Racing 10W-60 Change every 15000 km/ 12 months CLIMATE VSE CLIMATE Severe Mediterranean PRODUCT RECOMMENDATION 1 Image: Climate Bi-Turbo 20W-50 Climate Change every 15000 km/ 6 months Climate USE Climate Severe Mediterranean PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Bi-Turbo 20W-50 PRODUCT RECOMMENDATION 3 PRODUCT RECOMMENDATION 3 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Funder of SW-40 PRODUCT RECOMMENDATION 3 PROPOLICI RECOMMENDATION 3 | USE | | CLIMATE |
| Helar 0W-40 Emperol 5W-40 Emperol Racing 10W-60 Change every 15000 km/ 12 months USE CLIMATE VSE CLIMATE Mediterranean PRODUCT RECOMMENDATION 1 Image every 15000 km/ 6 months Image every 15000 km/ 6 months Change every 15000 km/ 6 months CLIMATE Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Emperol 5W-40 Emperol 5W-40 Emperol Racing 10W-60 | Normal | | Moderate |
| Change every 15000 km/ 12 months USE CLIMATE Severe Mediterranean PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 Change every 15000 km/ 6 months USE Change every 15000 km/ 6 months USE CLIMATE Severe Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 Helar 0W-40 PRODUCT RECOMMENDATION 2 Emperol 5W-40 Emperol 5W-40 Emperol Racing 10W-60 | PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| USE CLIMATE Severe Mediterranean PRODUCT RECOMMENDATION 1 Mediterranean Bi-Turbo 20W-50 Image avery 15000 km/ 6 months Change every 15000 km/ 6 months CLIMATE USE CLIMATE Severe Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Helar 0W-40 Emperol 5W-40 | Helar 0W-40 | Emperol 5W-40 | Emperol Racing 10W-60 |
| Severe Mediterranean PRODUCT RECOMMENDATION 1 Image of the second se | Change every 15000 km/ 12 months | | |
| PRODUCT RECOMMENDATION 1 Image of the second se | USE | | CLIMATE |
| Bi-Turbo 20W-50 Image: Severe severy 15000 km/ 6 months Use CLIMATE Severe Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Helar 0W-40 Emperol 5W-40 Emperol Racing 10W-60 | Severe | | Mediterranean |
| Change every 15000 km/ 6 months USE CLIMATE Severe Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Helar 0W-40 Emperol 5W-40 Emperol Racing 10W-60 | PRODUCT RECOMMENDATION 1 | | |
| USE CLIMATE Severe Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Helar 0W-40 Emperol 5W-40 Emperol Racing 10W-60 | Bi-Turbo 20W-50 | | |
| Severe Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Helar 0W-40 Emperol 5W-40 Emperol Racing 10W-60 | Change every 15000 km/ 6 months | | |
| PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Helar 0W-40 Emperol 5W-40 Emperol Racing 10W-60 | USE | | CLIMATE |
| Helar 0W-40Emperol 5W-40Emperol Racing 10W-60 | Severe | | Moderate |
| | PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Change every 15000 km/ 6 months | Helar 0W-40 | Emperol 5W-40 | Emperol Racing 10W-60 |
| | Change every 15000 km/ 6 months | | |

| DIFFERENTIAL REAR Capacity: 1,2 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Gearlube LS 80W-90 | |

Check every 15000 km/ 12 months

| TRANSMISSION AUTOMATIC 4/1 Capacity: 5,5 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| ATF Dexron II-D | |
| Change every 36 months | · |

1

OPEL OMEGA A V87 OMEGA A 1.8I (1986-1993)



| TRANSMISSION MANUAL 5/1 Capacity: 1,9 liter | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011 | SP Gear 5015 | Syngear TDL 75W-90 |
| | | |

Check every 15000 km/ 12 months

| HYDRAULIC BRAKE SYSTEM | | | |
|---------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | | |

Change every 12 months

| POWER STEERING | |
|--------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| ATF Dexron II-D | |

| COOLING SYSTEM Capacity: 6,4 liter | |
|---------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Coolant -38 Organic NF | |
| Change every 24 months | · |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.