OPEL OMEGA A V87 OMEGA A 2.3 TD (66 KW) (1986-1988)



ormal RODUCT RECOMMENDATION 1		Mediterranean
RODUCT RECOMMENDATION 1		wediterranean
i-Turbo 20W-50		
hange every 7500 km/ 12 months		
SE .		CLIMATE
ormal		Moderate
RODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
elar 0W-40	Emperol 5W-40	Emperol Racing 10W-60
hange every 7500 km/ 12 months		
SE		CLIMATE
evere		Mediterranean
RODUCT RECOMMENDATION 1		
i-Turbo 20W-50		
hange every 7500 km/ 6 months		
SE		CLIMATE
evere		Moderate
RODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
elar 0W-40	Emperol 5W-40	Emperol Racing 10W-60
hange every 7500 km/ 6 months		

DIFFERENTIAL REAR Capacity: 1,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Check every 15000 km/ 12 months	<u> </u>

TRANSMISSION AUTOMATIC 4/1 Capacity: 5,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 36 months	

OPEL OMEGA A V87 OMEGA A 2.3 TD (66 KW) (1986-1988)



TRANSMISSION MANUAL 5/1 Capacity: 1,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Syngear TDL 75W-90

Check every 15000 km/ 12 months

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Change every 12 months	'	'

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

COOLING SYSTEM Capacity: 10,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 24 months	'

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.