OPEL VECTRA A J89 VECTRA 2.0I 16V

(1994-1995)



ENGINE X20XEV Capacity: 4 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Bi-Turbo 20W-50	

Change every 15000 km/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar 0W-40	Emperol 5W-40	Emperol Racing 10W-60

Change every 15000 km/ 12 months

TRANSAXLE AUTOMATIC 4/1 Capacity: 3,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 36 months	·

TRANSAXLE MANUAL 5/1 Capacity: 1,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	
Check every 15000 km/ 12 months	'	,

HYDRAULIC BRAKE SYSTEM Capacity: 0,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Change every 12 months		·

OPEL VECTRA A J89 VECTRA 2.0I 16V

(1994-1995)



POWER STEERING Capacity: 0,9 liter	
use Normal	CLIMATE Moderate
PRODUCT RECOMMENDATION 1	INIOGETALE
ATF Dexron II-D	

COOLING SYSTEM Capacity: 7,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 24 months	·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.