## PEUGEOT 205 205 1.3 (1987-1991)



| ENGINE G1 Capacity: 3,3 liter, Filter capacity: 0,5 liter |                          |                          |  |  |
|---|--------------------------|--------------------------|--|--|
| USE   |                          | CLIMATE                  |  |  |
| Normal  |                          | Moderate                 |  |  |
| PRODUCT RECOMMENDATION 1                                  | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |  |  |
| Specialsynth MSP 5W-40                                    | Emperol 5W-40            | Asyntho 5W-30            |  |  |
| Check every 3000 km, change every 10000 km/ 12 months     |                          |                          |  |  |
| USE   |                          | CLIMATE                  |  |  |
| Severe  |                          | Moderate                 |  |  |
| PRODUCT RECOMMENDATION 1                                  | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |  |  |
| Specialsynth MSP 5W-40                                    | Emperol 5W-40            | Asyntho 5W-30            |  |  |

Change every 5000 km/6 months

| TRANSAXLE MANUAL 4/1 Capacity: 1,8 liter |                          |          |
|--|--------------------------|----------|
| USE                                      |                          | CLIMATE  |
| Normal                                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1                 | PRODUCT RECOMMENDATION 2 |          |
| SP Gear 5015                             | Gearlube RPC 75W-80      |          |
| Check every 60000 km                     | '                        | '        |

| HYDRAULIC BRAKE SYSTEM  |                          |          |
|---|--------------------------|----------|
| USE   |                          | CLIMATE  |
| Normal  |                          | Moderate |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 |          |
| Drauliquid-LV Super DOT 4                                       | Drauliquid-S DOT 4       |          |
| Chack every 10000 km/12 months, change every 40000 km/24 months |                          |          |

Check every 10000 km/ 12 months, change every 40000 km/ 24 months

| COOLING SYSTEM Capacity: 7 liter  |          |
|-----------------------------------|----------|
| USE                               | CLIMATE  |
| Normal                            | Moderate |
| PRODUCT RECOMMENDATION 1          |          |
| Coolant -38 Organic NF            |          |
| Change every 120000 km/ 24 months |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.