PRODUCT RECOMMENDATION

PEUGEOT 306 306 2.0 (1993-1996)

ENGINE XU10J2C

Capacity: 4,5 liter, Capacity: 4,25 liter (+ airconditioning), Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Specialsynth MSP 5W-40	**Emperol 5W-40**	**Asyntho 5W-30**

Change every 15000 km/ 12 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Specialsynth MSP 5W-40	**Emperol 5W-40**	**Asyntho 5W-30**

Change every 10000 km/ 6 months

TRANSAXLE MANUAL 5/1

Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 5015	**Gearlube RPC 75W-80**

Check every 60000 km

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**

Change every 60000 km/ 24 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

PEUGEOT 306 306 2.0 (1993-1996)

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 15000 km/ 12 months		

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 10000 km/ 12 months		

COOLING SYSTEM

Capacity: 7 liter, Capacity: 7,5 liter (with automatic transmission)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Change every 120000 km/ 24 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367