

PEUGEOT 308 T7 308 1.6 16V VTI THP (110 KW) 5FX (2007-2009)



MOTOR EP6DT
Kapacitet: 4,3 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Avanza MSP 0W-30

Skift alle 30000 km/ 24 måneder

ANVEND
Krævende

KLIMA
Moderat

PRODUKTANBEFALING 1
Avanza MSP 0W-30

Skift alle 20000 km/ 12 måneder

TRANSAKSEL AUTOMATISK AL4 4/1
Kapacitet: 5,9 liter (Førstegangsfyldning), Kapacitet: 3 liter (Servicepåfyldning)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Matic 2032

Kontroller alle 24 måneder/ 30000 km

ANVEND
Krævende

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Matic 2032

Kontroller alle 20000 km/ 12 måneder

TRANSAKSEL HALVAUTOMATISK MCP 6/1
Kapacitet: 1,8 liter (Servicepåfyldning), Kapacitet: 2 liter (Tør efterfyld)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1 SP Gear 5015	PRODUKTANBEFALING 2 Gearlube RPC 75W-80
--	---

Kontroller alle 24 måneder/ 30000 km

ANVEND
Krævende

KLIMA
Moderat

PRODUKTANBEFALING 1 SP Gear 5015	PRODUKTANBEFALING 2 Gearlube RPC 75W-80
--	---

Kontroller alle 20000 km/ 12 måneder

PEUGEOT 308 T7 308 1.6 16V VTI THP (110 KW) 5FX (2007-2009)



TRANSAXSEL MANUEL BE4/5 5/1

Kapacitet: 1,8 liter (Servicepåfyldning), Kapacitet: 1,9 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Gearlube RPC 75W-80	

Kontroller alle 24 måneder/ 30000 km

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Gearlube RPC 75W-80	

Kontroller alle 20000 km/ 12 måneder

GEARKASSE FOR HYDRAULISK AKTIVERING

Kapacitet: 0-0 liter (Påfyld indtil MAX)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Fluid 3023		

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Skift alle 24 måneder

ELEKTRISK-HYDRAULISK SERVOSTYRING (EHPS)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Fluid 3013		

PEUGEOT 308 T7 308 1.6 16V VTI THP (110 KW) 5FX (2007-2009)



KØLESYSTEM

Kapacitet: 6,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 24 måneder/ 30000 km

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 20000 km/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.