

PEUGEOT 308 T7 308 1.6 16V VTI THP (110 KW) 5FX (2007-2009)



ENGINE EP6DT
Capacity: 4,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Avanza MSP 0W-30

Change every 30000 km/ 24 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Avanza MSP 0W-30

Change every 20000 km/ 12 months

TRANSAXLE AUTOMATIC AL4 4/1
Capacity: 5,9 liter (Initial fill), Capacity: 3 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

Check every 24 months/ 30000 km

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

Check every 20000 km/ 12 months

TRANSAXLE MANUAL BE4/5 5/1
Capacity: 1,9 liter (Dry fill), Capacity: 1,8 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

Check every 24 months/ 30000 km

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

Check every 20000 km/ 12 months

PEUGEOT 308 T7 308 1.6 16V VTI THP (110 KW) 5FX (2007-2009)


TRANSAXLE SEMI-AUTOMATIC MCP 6/1

Capacity: 2 liter (Dry fill), Capacity: 1,8 liter (Service fill)

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80*Check every 24 months/ 30000 km*

USE		CLIMATE
Severe		Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80*Check every 20000 km/ 12 months*
HYDRAULIC ACTUATION MCP GEARBOX

Capacity: 0-0 liter (Fill until MAX)

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3023
HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Change every 24 months*
ELECTRO-HYDRAULIC POWER STEERING (EHPS)

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013

PEUGEOT 308 T7 308 1.6 16V VTI THP (110 KW) 5FX (2007-2009)



COOLING SYSTEM

Capacity: 6,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Check every 24 months/ 30000 km

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Check every 20000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.