

**PEUGEOT 405 405 1.6 (1992-1993)****ENGINE** XU52C/K ,XU5M3/L/Z, XU5JP/L/Z

Capacity: 5,5 liter, Capacity: 5 liter (+ aluminium carter/oil pan), Filter capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Specialsynth MSP 5W-40</b>	<b>Emperol 5W-40</b>	<b>Asyntho 5W-30</b>

*Check every 3000 km, change every 10000 km/ 12 months*

USE		CLIMATE
Severe		Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Specialsynth MSP 5W-40</b>	<b>Emperol 5W-40</b>	<b>Asyntho 5W-30</b>

*Change every 7500 km/ 6 months***TRANSAXLE AUTOMATIC** 4HP14 4/1

Capacity: 2,4 liter

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1		
<b>ATF Dexron II-D</b>		

*Check every 10000 km/ 12 months, change every 40000 km***TRANSAXLE MANUAL** 4/1

Capacity: 2 liter

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 5015</b>	<b>Gearlube RPC 75W-80</b>	

*Check every 60000 km***HYDRAULIC BRAKE SYSTEM**

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

*Check every 10000 km/ 12 months, change every 40000 km/ 24 months*

**PEUGEOT 405 405 1.6 (1992-1993)****POWER STEERING**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>ATF Dexron II-D</b>		

*Check every 20000 km*

**COOLING SYSTEM**

Capacity: 6,6-7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant -38 Organic NF</b>		

*Change every 120000 km/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*