PEUGEOT 405 405 1.9 TD (1992-1996)



ENGINE XUD9TE/L, XUD9TE/Y Capacity: 5 liter, Filter capacity: 0,5 liter					
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3			
Specialsynth MSP 5W-40	Emperol 5W-40	Asyntho 5W-30			
Check every 3000 km, change every 10000 km/ 12 months					
USE		CLIMATE			
Severe		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3			
Specialsynth MSP 5W-40	Emperol 5W-40	Asyntho 5W-30			
Change every 7500 km/ 6 months					

TRANSAXLE MANUAL 5/1 Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube RPC 75W-80	
Check every 60000 km		

HYDRAULIC BRAKE SYSTEM				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			

Check every 10000 km/12 months, change every 40000 km/24 months

POWER STEERING			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
ATF Dexron II-D			
Check every 20000 km			

PEUGEOT 405 405 1.9 TD (1992-1996)



COOLING SYSTEM Capacity: 7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	
Change every 120000 km/24 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.