

PEUGEOT 407 407 2.2 16V KOX (2004-2009)**ENGINE EW12J4**

Capacity: 4,25 liter, Filter capacity: 0,25 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Specialsynth MSP 5W-40 | Emperol 5W-40 | Asyntho 5W-30 |

Change every 30000 km/ 24 months

| USE | | CLIMATE |
|-------------------------------|--------------------------|--------------------------|
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Specialsynth MSP 5W-40 | Emperol 5W-40 | Asyntho 5W-30 |

*Change every 20000 km/ 12 months***TRANSAXLE AUTOMATIC 4HP20 4/1**

Capacity: 3 liter (Service fill)

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 2032 | | |

TRANSAXLE MANUAL ML6C 6/1

Capacity: 2,6 liter

| USE | | CLIMATE |
|--------------------------|----------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Gear 5015 | Gearlube RPC 75W-80 | |

Check every 48 months/ 60000 km

| USE | | CLIMATE |
|--------------------------|----------------------------|----------|
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Gear 5015 | Gearlube RPC 75W-80 | |

Check every 40000 km/ 24 months

**HYDRAULIC BRAKE SYSTEM ABS**

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|----------------------------------|---------------------------|
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 |

Check every 30000 km, change every 60000 km/ 24 months

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|----------------------------------|---------------------------|
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 |

Check every 20000 km/ 12 months, change every 60000 km/ 24 months

POWER STEERING

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | |
|--------------------------|--|
| SP Fluid 3013 | |

Check every 24 months/ 30000 km

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1 | |
|--------------------------|--|
| SP Fluid 3013 | |

Check every 20000 km/ 12 months

COOLING SYSTEM

Capacity: 7,9 liter, Capacity: 1,6 liter (Reservoir), Capacity: 8,4 liter (with automatic transmission)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | |
|--------------------------|--|
| Coolant SP 14+ | |

Check every 24 months/ 30000 km

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1 | |
|--------------------------|--|
| Coolant SP 14+ | |

Check every 15000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.