

# PEUGEOT 508 508 1.6I 16V THP (110 KW) 5FE, 5FN (2011-2012)

**ENGINE EP6CDT**

Capacity: 4,25 liter, Filter capacity: 0,25 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

**Avanza MSP 0W-30***Change every 30000 km/ 24 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

**Avanza MSP 0W-30***Change every 20000 km/ 12 months***TRANSAXLE AUTOMATIC AT6 6/1**

Capacity: 7 liter (Dry fill), Capacity: 3 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 4036****TRANSAXLE MANUAL MCM 6/1**

Capacity: 2,2 liter (Dry fill), Capacity: 2,1 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 5015**

PRODUCT RECOMMENDATION 2

**Gearlube RPC 75W-80****HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4***Change every 24 months*

# PEUGEOT 508 508 1.6l 16V THP (110 KW) 5FE, 5FN (2011-2012)



## ELECTRO-HYDRAULIC POWER STEERING (EHPS)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Fluid 3013</b>		

## COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 14+</b>		

*Change every 120000 km/ 48 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*