PEUGEOT 508 508 2.0 HDI 16V (120 KW) DPF RHD, RHH (2012-2015)



ENGINE DW10CTED4 Capacity: 5 liter (Orange dipstick), Capacity: 5,5 liter (Yellow dipstick), Filter capacity: 0,25 liter			
USE		CLIMATE	
Flexible (max)		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Avanza MSP 0W-30	Presteza MSP 5W-30	Avanza MSP+ 5W-30	
Change every 30000 km/ 24 month	IS IS	· · · ·	
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Avanza MSP 0W-30	Presteza MSP 5W-30	Avanza MSP+ 5W-30	

Change every 20000 km/ 12 months

TRANSAXLE AUTOMATIC AM6 6/1 Capacity: 7 liter (Dry fill), Capacity: 4 liter (Service fill)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4036			

TRANSAXLE MANUAL ML6C 6/1 Capacity: 2,2 liter (Dry fill with fins), Capacity: 2,9 liter (Dry fill without fins), Capacity: 1,9 liter (Service fill with fins), Capacity: 2,6 liter (Service fill without fins)		
use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 SP Gear 1081		

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		
Change every 24 months		

PEUGEOT 508 508 2.0 HDI 16V (120 KW) DPF RHD, RHH (2012-2015)



ELECTRO-HYDRAULIC POWER STEERING (EHPS)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Fluid 3013			

COOLING SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant SP 14+			
Change every 120000 km/ 48 months			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.