PEUGEOT 508 508 GT 2.2 HDI 16V DPF 4HL (2012-2015)



ENGINE DW12C Capacity: 4,85-5,25 liter, Filter capa	acity: 0,25 liter	
use Flexible (max)		CLIMATE
		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Avanza MSP 0W-30	Presteza MSP 5W-30	Avanza MSP+ 5W-30
Change every 30000 km/ 24 month	IS International	
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Avanza MSP 0W-30	Presteza MSP 5W-30	Avanza MSP+ 5W-30

Change every 20000 km/ 12 months

TRANSAXLE AUTOMATIC AM6 6/1 Capacity: 7 liter (Dry fill), Capacity: 4 liter (Service fill)				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
SP Matic 4036				

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Drauliquid-LV Super DOT 4				

Change every 24 months

ELECTRO-HYDRAULIC POWER STEERING (EHPS)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Fluid 3013				

information contained herein is subject to changes without notification.

PEUGEOT 508 508 GT 2.2 HDI 16V DPF 4HL (2012-2015)



COOLING SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant SP 14+			
Change every 120000 km/ 48 months			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

KROON-OIL B.V. Postbus 149 7600 AC Almelo