## PEUGEOT 806 806 1.9 TD (1994-1994)



ENGINE XUD9TF/XUD9BTF Capacity: 4,25 liter, Capacity: 4 liter (+ airconditioning), Filter capacity: 0,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Specialsynth MSP 5W-40	Emperol 5W-40	Asyntho 5W-30	
Check every 3000 km, change every 10000 km/ 12 months			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Specialsynth MSP 5W-40	Emperol 5W-40	Asyntho 5W-30	

Change every 5000 km/ 6 months

TRANSAXLE MANUAL ME5K 5/1 Capacity: 1,85 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube RPC 75W-80	
QL = - L =		

Check every 60000 km/24 months

TRANSAXLE MANUAL ML5T 5/1 Capacity: 1,85 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube RPC 75W-80	

Check every 60000 km/ 24 months

HYDRAULIC BRAKE SYSTEM ABS AS OPTION			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Change every 40000 km/ 48 months		-	

## PEUGEOT 806 806 1.9 TD (1994-1994)



POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Check every 10000 km/ 12 months	

COOLING SYSTEM Capacity: 9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Check every 10000 km/ 12 months, change every 120000 km/ 24 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.