## PEUGEOT 806 806 2.01 (1995-1998)



ENGINE XU10J2C Capacity: 4,75 liter, Filter capacity: 0,5 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Specialsynth MSP 5W-40	Emperol 5W-40	Asyntho 5W-30		

Change every 15000 km/ 12 months

TRANSAXLE MANUAL BE3/5 5/1 Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube RPC 75W-80	

Check every 60000 km/ 12 months

HYDRAULIC BRAKE SYSTEM ABS AS OPTION Capacity: 0,47 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			

Check every 15000 km/ 12 months, change every 60000 km/ 24 months

POWER STEERING			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
ATF Dexron II-D			

Check every 15000 km/ 12 months

COOLING SYSTEM Capacity: 8,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Check even (15000 km/12 months, chapter even (120000 km/24 months)		

Check every 15000 km/ 12 months, change every 120000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the **PRODUCT RECOMMENDATION** 

PEUGEOT 806 806 2.01 (1995-1998)



information contained herein is subject to changes without notification.